GALACTIC E900 10W-40

PRODUCT DESCRIPTION

GALACTIC E900 10W-40 is a high-performance diesel engine lubricant with synthetic HC technology, developed for latest generation Heavy Duty engines requiring Low SAPS oils compatible with advanced emission treatment systems.

This oil is specially formulated for engines meeting Euro V and Euro VI standards, equipped with diesel particulate filters (DPF), exhaust gas recirculation (EGR), and selective catalytic reduction (SCR) systems.

Its Low SAPS technology, with low content of sulfated ash, phosphorus, and sulfur, protects post-treatment systems and helps extend the service life of the engine's anti-pollution components.

Thanks to its high thermal stability and oxidation resistance, GALACTIC E900 10W-40 lubricant ensures reliable lubrication even under extremely severe conditions such as high loads, dust, high temperatures, or long continuous operating periods. This oil has been developed to withstand extended oil change intervals, keeping the engine clean, reducing wear, and ensuring optimal performance even when using low-quality fuels or biodiesel.

Main advantages

- Low SAPS technology compatible with DPF, EGR, and SCR
- Excellent engine protection under severe conditions
- High thermal stability and oxidation resistance
- Excellent wear control and engine cleanliness
- Allows extended oil change intervals
- Reduces deposit and sludge formation
- Excellent performance under high loads and long working hours

Applications

Especially recommended for:

Trucks and industrial vehicles

Construction and mining machinery

Off-Road equipment

Railway equipment

Generators and heavy machinery

Suitable for modern diesel engines from manufacturers:

Komatsu, Hitachi, JCB, Kobelco, Isuzu, Iveco, among others.

Also suitable for On-Road and Off-Road engines requiring ACEA E9 or API CJ-4 lubricants.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L

GALACTIC E900 10W-40

PRESENTATION

Bulk	110087
1000 LTS.	100322
200 LTS.	100323
50 LTS.	100324
20 LTS.	100325
5 LTS.	100336
4 LTS.	110085
1 LT.	

QUALITY LEVEL

ACEA E7,E9,E11
API: CJ-4/SN
VOLVO: VDS-4/VDS-3
MACK EO – M+
MAN M 3575/3275
RENAULT RVI RLD-3
MTU Type 2.1
MB 228.31/228.3
Cummins CES 20081
SCANIA Low Ash
CAT ECF 1A,2A,3

TECHNICAL PROPERTIES

Property	Value
SAE GRADE	10W-40
VISCOSITY AT 100°C	12,5-16,3
VISCOSITY AT -25°C	<7000
VISCOSITY INDEX	150
FLASH POINT	225
POUR POINT	-35
SULPHATED ASH	<1,0
TBN	7

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L

SAFETY AND HYGIENE

Safety Data Sheets are available upon request and should be consulted for detailed information on the proper handling and use of the product. The company is not responsible for damages resulting from improper use or failure to comply with the indicated precautions and recommendations.

IMPORTANT NOTE

The information presented is based on current production data and may vary within the specified tolerances. Temperature ranges are provided as a guideline. The information and data contained in this document may be changed without prior notice. This information replaces and voids all previous editions.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L