FLAGSHIP 952
0W-20

PRODUCT DESCRIPTION

Aceite de motor 0W-20 100% sintético de rendimiento Premium, desarrollado para cumplir con las exigencias de los motores Ford modernos, especialmente los motores EcoBlue diésel de 1.5L, así como una amplia gama de vehículos híbridos de última generación.
Su avanzada formulación con bases sintéticas de alta calidad y aditivos de última generación proporciona máxima eficiencia energética, reducción del consumo de combustible y menores emisiones de CO_2, contribuyendo al cumplimiento de las normativas medioambientales actuales.
Gracias a su baja viscosidad y excelente fluidez en frío, este lubricante garantiza una circulación extremadamente rápida del aceite tras el arranque, reduciendo el desgaste del motor y proporcionando una protección superior desde el primer momento.
Este aceite 0W-20 de última generación ofrece además una gran estabilidad térmica, resistencia a la oxidación y excelentes reservas de rendimiento incluso en condiciones de conducción exigentes.
Está especialmente diseñado para cumplir con los estrictos requisitos de la especificación FORD WSS-M2C952-A1, necesaria para motores Ford EcoBlue, así como otras especificaciones utilizadas por fabricantes como Mercedes-Benz, Opel, Jaguar Land Rover y General Motors.

Main Advantages
- Maximum fuel savings and energy efficiency
- Reduction of CO_2 emissions
- Excellent protection against engine wear
- Fast cold start with immediate oil circulation
- High thermal stability and oxidation resistance
- Compatible with modern hybrid vehicles
- Keeps the engine clean thanks to its high detergent capacity

Applications
Oil especially recommended for:
Ford EcoBlue diesel 1.5L engines
Hybrid vehicles (HEV, PHEV, MHEV)
Modern low-consumption passenger cars
Vehicles requiring ACEA C5 / C6 oils
Selected models from Ford, Mercedes-Benz, Opel, Jaguar Land Rover, and GM

PRESENTATION

BULK	111983
1000 LTS.	111972
200 LTS.	111976
50 LTS.	111978
20 LTS.	111979
5 LTS.	111980
4 LTS.	111981
1 LT.	111982

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L

QUALITY LEVEL

ACEA C5,C6
ILSAC GF-5
API SN PLUS/SP
MB 229.72
OPEL OV 040 1547
GM DEXOS D
JLR 03.5006
JLR 51.5122
FORD WSS-M2C952-A1 / FORD WSS-M2C947-A / FORD WSS-M2C947-B1 / FORD WSS-M2C962-A1 / FORD WSS-M2C954 A1

TECHNICAL PROPERTIES

Property	Value
SAE GRADE	0W-20
VISCOSITY AT 40°C	38,7
VISCOSITY AT 100°C	8,1
VISCOSITY INDEX	>170
VISCOSITY AT -35°C	<6200
DENSITY AT 20°C	0,845
HTHS	>2,6
FLASH POINT	>210
POUR POINT	-45

SAFETY AND HYGIENE

Safety Data Sheets are available upon request and should be consulted for detailed information on the proper handling and use of the product. The company is not responsible for damages resulting from improper use or failure to comply with the indicated precautions and recommendations.

IMPORTANT NOTE

The information presented is based on current production data and may vary within the specified tolerances. Temperature ranges are provided as a guideline. The information and data contained in this document may be modified without prior notice. This information replaces and voids all previous editions.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L