# FLAGSHIP C23 5W-30

## PRODUCT DESCRIPTION

FLAGSHIP C23 5W-30 is a 100% synthetic high-performance engine lubricant, developed to offer maximum protection, efficiency, and power in modern gasoline and diesel engines. Current anti-pollution regulations demand increasingly efficient engines, capable of generating greater power while reducing fuel consumption and emissions. In this context, the lubricant plays a key role in reducing friction and optimizing engine performance.

Thanks to its advanced formulation with synthetic bases and latest generation additives, FLAGSHIP C23 5W-30 provides excellent pressure resistance, maintaining a stable lubricating film even under demanding driving conditions. This oil is designed to reduce energy losses caused by friction between internal engine components, allowing better use of available power and improving the vehicle's overall efficiency.

Its advanced technology also helps keep the engine clean and protected against wear, ensuring reliable operation over long service intervals.

Main advantages
- Greater engine power and response
- Improves energy efficiency and fuel consumption
- Excellent protection against wear and friction
- High pressure resistance in modern engines
- Keeps the engine clean and deposit-free
- Excellent thermal stability and oxidation resistance
- Compatible with modern gasoline and diesel engines

Applications
Especially recommended for:
Modern gasoline and diesel vehicles
Engines with turbo and direct injection
Vehicles requiring ACEA C2, C3 lubricants
High-performance passenger cars and light vehicles
Suitable for a wide range of European and Asian manufacturers.

## PRESENTATION

| | |
|---|---|
| Bulk | 108621 |
| 1000 LTS. | 106275 |
| 200 LTS. | 106276 |
| 50 LTS. | 106277 |
| 20 LTS. | 106278 |
| 5 LTS. | 106279 |
| 4 LTS. | 109142 |
| 1 LT. | 107669 |

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L

## QUALITY LEVEL

ACEA C2,C3
API: SN+/CF
PSA B71 2290
GM DEXOS 2
FIAT 9.55535-S1
FIAT 9.55535-S2
VW 502.00/505.01
Renault RN0700
MB 229.52
STELLANTIS FPW9.55535/03

## TECHNICAL PROPERTIES

| Property | Value |
|---|---|
| SAE GRADE | 5W-30 |
| VISCOSITY AT 100°C | 9.3-12.5 |
| VISCOSITY AT -30°C | <6600 |
| HTHS-150°C | >3.5 |
| VISCOSITY INDEX | 155 |
| FLASH POINT | 234 |
| POUR POINT | -45 |
| SULPHATED ASH | <0.8 |
| TBN | >6.0 |

## SAFETY AND HYGIENE

Safety Data Sheets are available upon request and should be consulted for detailed information on the proper handling and use of the product. The company is not responsible for damages resulting from improper use or failure to comply with the indicated precautions and recommendations.

## IMPORTANT NOTE

The information presented is based on current production data and may vary within the specified tolerances. Temperature ranges are provided as a guideline. The information and data contained in this document may be changed without prior notice. This information replaces and voids all previous editions.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

*The SASH brand and design are registered trademarks of ACEITES LUBRICANTES SASH,S.L*